

REVERSED EYE RE – Type 6







FLAT EYE FE – Type 7



RE TYPE 6-- These are exceptionally durable slings that feature full body and eye protection. Eye openings are 90° to the sling body for tighter choker hitches and easy vertical and basket hitch rigging.



FE TYPE 7--These slings are the same construction as Reversed Eyes with one exception: the eyes are on the same plane as the sling body. Flat eye permits rigging through narrower openings and easier removal from under loads. These slings also rig effectively in choker and basket hitches.

Stock No. <i>(* start with RE or FE)</i>	Width (inches)	Ply	Rated Capacities in Pounds						Taper	
			Vertical 	Choker 	Basket Hitch				Width W (inches)	Length L (inches)
						60° 	45° 	30° 		
*-1-902	2	1	3,100	2,480	6,200	5,369	4,383	3,100	1	9
*-2-902	2	2	6,200	4,960	12,400	10,738	8,767	6,200	1	12
*-1-904	4	1	6,200	4,960	12,400	10,738	8,767	6,200	2	12
*-2-904	4	2	12,400	9,920	24,800	21,477	17,534	12,400	2	12
*-3-904	4	3	16,500	13,200	33,000	28,380	23,265	16,500	2	15
*-4-904	4	4	22,000	17,600	44,000	38,104	31,108	22,000	2	15
*-1-906	6	1	9,400	7,520	18,800	16,281	13,262	9,400	1-1/2	12
*-2-906	6	2	17,600	14,080	35,200	30,483	24,866	17,600	1-1/2	15
*-3-906	6	3	24,700	19,800	49,400	42,484	34,827	24,700	3	18
*-4-906	6	4	32,900	26,320	65,800	56,983	46,521	32,900	3	18

* Insert RE prefix to indicate Type 6 and FE prefix to indicate Type 7.

* Polyester Webbing standard, unless otherwise requested

Warning: Horizontal sling angles less than 30° shall not be used.